Proposed New Home For

Willis & Megan Williams 19 Austin Drive Whitianga





Wind = **HIGH** Earthquake = **ZONE 1** Corrision = ZONE D Snow = UP to 1.0kPa

John Ottaway




DRAWING SHEET INDEX

		SHEET	CURRENT
SHEET	SHEET NAME	SIZE	ISSUE
<i>O</i> 1	TITLE	420 / 297	02
02	SHEET INDEX / CHANGES	420 / 297	<i>O</i> 2
03	STANDARD NOTES	420 / 297	<i>O</i> 2
04	SITE SAFETY	420 / 297	<i>0</i> 2
<i>0</i> 5	3D VIEW 1	420 / 297	<i>O</i> 2
06	3D VIEW 2	420 / 297	<i>O</i> 2
07	3D VIEW 3	420 / 297	<i>O</i> 2
08	3D VIEW 4	420 / 297	<i>O</i> 2
09	3D VIEW 5	420 / 297	<i>O</i> 2
10	SITE PLAN	420 / 297	<i>O</i> 2
11	DRAINAGE PLAN	420 / 297	<i>O</i> 2
12	DRAINAGE DETAILS	420 / 297	02
13	SETOUT PLAN	420 / 297	02
14	FOUNDATION PLAN	420 / 297	<i>O</i> 2
15	RIBRAFT FOOTING DETAILS O1	420 / 297	<i>O</i> 2
16	RIBRAFT FOOTING DETAILS 02	420 / 297	<i>O</i> 2
17	RIBRAFT FOOTING DETAILS 03	420 / 297	<i>O</i> 2
18	RIBRAFT FOOTING DETAILS 04	420 / 297	<i>O</i> 2
19	RIBRAFT FOOTING DETAILS 05	420 / 297	<i>O</i> 2
20	FLOOR PLAN	420 / 297	<i>O</i> 2
21	ELEVATIONS	420 / 297	<i>O</i> 2
22	DIMENSION PLAN	420 / 297	<i>O</i> 2
23	ROOF FRAMING PLAN	420 / 297	<i>O</i> 2
24	CEILING PLAN	420 / 297	<i>O</i> 2
25	ROOFING PLAN	420 / 297	<i>O</i> 2
26	BRACING PLAN	420 / 297	<i>O</i> 2
27	BRACING CALCS	420 / 297	<i>O</i> 2
28	ELECTRICAL PLAN	420 / 297	<i>O</i> 2
29	FLOOR COVERING PLAN	420 / 297	<i>O</i> 2
30	SECTION A-A	420 / 297	<i>O</i> 2
31	SECTION B-B	420 / 297	<i>O</i> 2

DRAWING SHEET INDEX

SHEET	SHEET NAME	SHEET SIZE	CURRENT ISSUE
32	SECTION C-C	420 / 297	<i>O</i> 2
33	EXTERIOR DOOR & WINDOW SCHEDULE	420 / 297	<i>O</i> 2
34	DURABILITY	420 / 297	<i>O</i> 2
35	LINTEL FIXINGS 1	420 / 297	<i>O</i> 2
36	LINTEL FIXINGS 2	420 / 297	<i>O</i> 2
37	PURLIN FIXING / BRICK TIES	420 / 297	<i>O</i> 2
38	TOP € BOTTEM PLATE FIXINGS	420 / 297	<i>O</i> 2
39	MISC DETAILS	420 / 297	<i>O</i> 2
40	WINDOW TAPE DETAILS	420 / 297	<i>O</i> 2
41	ROOFING DETAILS 1	420 / 297	<i>O</i> 2
42	ROOFING DETAILS 2	420 / 297	<i>O</i> 2
43	ROOFING DETAILS 3	420 / 297	<i>O</i> 2
44	BRICK VENEER DETAILS 01	420 / 297	<i>O</i> 2
45	BRICK VENEER DETAILS 02	420 / 297	<i>O</i> 2
46	BRICK VENEER DETAILS 03	420 / 297	<i>O</i> 2
47	BRICK VENEER DETAILS 04	420 / 297	<i>O</i> 2
48	BRICK VENEER DETAILS 05	420 / 297	<i>O</i> 2
49	BRICK VENEER DETAILS 06	420 / 297	<i>O</i> 2
50	BRICK VENEER DETAILS 07	420 / 297	<i>O</i> 2
51	SHADOWCLAD DETAILS 01	420 / 297	<i>O</i> 2
52	SHADOWCLAD DETAILS 02	420 / 297	<i>O</i> 2
53	SHADOWCLAD DETAILS 03	420 / 297	<i>O</i> 2
54	BRACING DETAILS (Conc Floor)	420 / 297	<i>O</i> 2
55	BRACE DETAILS	420 / 297	<i>O</i> 2
56	BRACE DETAILS	420 / 297	<i>O</i> 2
57	WET AREA DETAILS	420 / 297	<i>O</i> 2
58	WET AREA DETAILS	420 / 297	<i>O</i> 2
59	WET AREA DETAILS	420 / 297	<i>O</i> 2







GENERAL NOTES

- THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS ON SITE PRIOR TO COMMENCEMENT OF ANY WORK. ANY DISCREPANCIES TO BE RAISED WITH DATAPLANWAIKATO.
- All work to be carried out in accordance with drawings and specification provided.
- It is the main contractors or surveyors responsibility to check and verify all dimensions and levels on site before commencement of work.
- All work shall comply with the NZBC, all relevant Local Authority bylaws, NZS 3604 2011, and all relevant standards
- The territorial authority shall be notified of any changes made during the construction
- All work to be undertaken to be best trade practice for each respective trade. Any substandard work or or building material defects shall be the Contractors responsibility to remove, repair or replace at no extra cost to the Client.
- All timber framing and exposed timber shall be treated to comply with NZS 3602: 2003.
- Ensure wall linings adjacent to appliances and facilities have surfaces that can be easily maintained in a hygienic condition in accordance with G3/AS1 clause 1.6.
- Ensure all selected tiling achieves slip resistance co-efficients as per D1/AS1 Table 2.

SITE NOTES

- Finished Ground levels adjoining the concrete slab on ground shall be formed so as to carry water away from the building, at a slope of 1 in 50, for a distance of at least 1.0m from the building.
- Level access routes shall have a mean co-efficient of friction μ of no less than 0.4 when tested in accordance with AS/NZS 3661.1 (Exposed Crushed Aggregate)

DRAINAGE NOTES

- All drains to comply with AS3500
- CONFIRM LOCATION OF SEWER & STORMWATERLATERALS PRIOR TO ANY EXCAVATION WORKS
- Potable water drawn from mains to be fitted with back flow preventer.
- All pipe penetrations through concrete shall be wrapped in DENSO TAPE or similar product to allow for pipe expansion & movement
- Air admittance valves are to be fitted to all fittings greater than 3.5 meters from gully traps
- Ensure hot water system valving complies with G12/AS1 clause 6.
- · Ensure equipotential bonding complies with G12/AS1 clause 9.
- The delivery of hot water to be 55° at the tap via use of a tempering valve. Set thermostat at 60° to prevent Legionella Bacteria occurring.

INSULATION NOTES

- Building Wrap shall be folded into the perimeter of all window and door openings to the inside face of the framing.
- All corners shall be taped and flexible flashing tape apllied to the head and the sill using the "Masons" window sealing system Head/sill & jamb flashings throughout
- 180m³/hr min mechanical extractor fan with Grease filter to Kitchen Cooktop.
- 90m³/hr min mechanical extractor Fans to Bathroom € laundry

FOUNDATION NOTES

- It is the main contractors or surveyors responsibility to check and verify all dimensions and levels on site beforecommencement of work
- · Dimensions are to SLAB EDGES Unless noted otherwise.
- Generally footings shall be taken down to solid, sound undisturbed soil of 300KPa bearing capacity. Excessive amounts of soil shall be reported to the structural engineer.
- · All reinforcing is to be Ductility Class E, in accordance with NZS 4671.
- Minimum slab reinforcing is to be 2.27kg/m2 welded reinforcing mesh sheets (1.15kg/m2 in each direction) lapped 225m, Suitable Mesh SuperDuctile Mesh, Fletcher Reinforcing, 6mm dia., 140 square mesh, grade 300E.
- Concrete strength for foundations, footings and slabs shall be 25MPa after 28days.
- · Concrete shall be cured for a minimum of 3 days
- · Slab shall have 70mm mesh edge cover
- Maximum slab gradual deviation from vertical 5.0mm over 3.0m for carpet (garage floor also) and all other areas 3.0mm over 3.0m.
- · Maximum Slab Abrupt deviation from vertical 5.0mm over 200mm.
- Maximum deviation from Level 5.0mm up to 10m, and 1.0mm over 10m
- Slab Granular Fill shall be compacted in 150mm layers to a maximum depth of 600mm
- Reinforcing steel shall have a cover of 30 mm minimum from the top surface of the ground slab and shall be placed in such a manner as to avoid damage to the DPM.
- Saw cutting shall take place no later than 24 hours after initial set for average ambient temperatures above 20 °C, and 48 hours for average ambient temperatures below 20 °C.

FRAMING NOTES

- · All timber shall be H1.2 treated graded SG8 unless stated otherwise.
- All timber framing and exposed timber shall be treated to comply with NZS 3602: 2004.
- All timber fixed to concrete shall be separated from concrete 'Malthoid' damp proof course.
- Bottom plate Hold downs are to be within 150mm of each end of wall frame and bracing panels. M10x140 Bowmac Blue Head Screw Bolt and 50x50x3 washers with 55mm edge cover @ 900mm c/c.
- Internal walls to be fixed with 75mm shot fired concrete pins at 600 crs. and within 150mm of ends of plates.
- Maximum Holes Tostuds or plates 25mm Dia. or rebates to studs or plates 25mm deep x 200mm long
- 5.0mm Plumb tolerance to wall framing refer to NZS 3604: 2011 Table 2.15.0mm Plumb tolerance to wall framing refer to NZS 3604: 2011 Table 2.1


WINDOW NOTES


- All glazing to be in accordance with NZS 4223: 2016 All Parts (Grade A Safety Glass were Shown).
- · Site measure all windows and doors beforefabrication.
- · All glazing units to achieve RO.26 min. And shall comply to NZS 4223.
- Exterior windows and doors viewed from exterior.
- Schedule to be read in conjunction with the elevations and the floor plans.
- Finish to be powdercoatedaluminium (scratchedjoinery will be rejected).
- · Timber jambs with Architrave
- Ensure continuous sill support to all joinery.
- Ensure continuous 'tight fit' backing rod for sealing around joinery openings.
- · Obscure glass to bathrooms Etchlite.
- · All to WANZ approved installation.
- · Single piece head flashing, not to be jointed.
- · Windows to the bathrooms/ensuite are openable.
- Mechanical ventilation shall be provided to the bathrooms/ensuite.

ELECTRICAL NOTES

- All electrical work and items are to comply with NZBC F7/AS1, AS/NZ3000, AS/NZS 3008, AS 3786 and NZS 6401.
- Final electrical Layout to be approved on site by Owner.
- · All Circuits to be on RCD's, lights on a separate RCD to other circuits.
- Ensure Lighting to provide a minimum Luminance of 20 lux per m2 of floor area is to be as shown in G8/AS1 table 1
- · Allow to install range hood and vent through soffit, Gable or roof.
- · Allow to install double socket for Waste disposal and Dishwasher.
- Allow to install Garage opener socket, and opener switch with garage light switch.
- · Garage sockets @ 1.0m above FFL to centre.
- · Allow to install water heater socket.
- · Bedside light switches shall be placed 650mm above FFL to centre.
- And all socket outlets are to be 500mm FFL to centre, 200mm above benches, 1700mm @ fridge above FLL to centre.
- All light switches are to be at between 900 1200mm above FFL to centre and must be horizontally lined up with door handles.
- Light switches and sockets to be either rocker/push pad/toggle or push button type.
- Approved smoke detectors required within 3.0m of any sleeping space.
- The smoke alarm shall be either hard wired or battery powered And shall provide a hush facility.
- Electrical Safety Regulation 2012 only IC LED downlights to be installed.
- · Downlight's to be IC-Rated Type (max. 1 per 5m²)









CONSTRUCTION AND DEMOLITION HAZARDS

Acceptable Solution F5/AS1

1.0 Work-Site Barriers

1.0.1 The necessity for barriers will depend mainly on the site location. The need will be greater in areas with high levels of pedestrian traffic (i.e. in Central Business Districts), than in industrial or rural areas. Barriers are not necessary for domestic dwellings up to 2 storeys above ground level unless specific hazards exist.

COMMENT:

At all work-sites hazard evaluation will take account of:

- 1. Pedestrian counts adjacent to the site.
- 2. Car parking adjacent to the site.
- 3. Location of neighbouring buildings.
- 4. Presence of neighbouring work-sites or recreation areas.
- 5. Proximity to schools or early childhood centres.
- 6. Proximity to housing.
- 7. The depth of a water hazard.
- 8. The period of time for which ponded water will be present.
- 9. The accessibility and 'visibility' of the site.
- 1.0.2 If a work-site is not completely enclosed, and unauthorised entry by children is likely, it is acceptable for specific hazards to be fenced only when workers are absent from the immediate vicinity.

1.0.3 Where the potential hazard at a work-site makes a safety barrier necessary, a barrier complying with Table 1 is an acceptable solution.

1.1 Site fences and hoardings

- **1.1.1** Fences and *hoardings* shall extend at least 2.0 m in height from ground level on the side accessible to the public.
- 1.1.2 An acceptable fence may be constructed with galvanised chainlink netting having a maximum sized grid of 50 mm x 50 mm. Post spacing shall be a maximum of 2.5 m, and the gap between the bottom of the fence and ground no greater than 100 mm.
- 1.1.3 Any hoarding shall have continuous cladding in any of the following materials:
- a) Close-butted timber with a thickness of at least 19 mm.
- b) 6.0 mm thick exterior grade plywood on studs spaced at no greater than 600 mm centres.
- c) 9.5 mm thick exterior grade plywood on studs spaced at no greater than 1000 mm
- d) Continuous metal cladding constructed with studs and rails spaced to provide strength and rigidity comparable with the hoardings in Paragraphs 1.1.3 a) to c).

Table 1:	Barriers for Different S Paragraph 1.0.3	ite Conditions	
	I distance of site boundary	Height of work above site boundary	Acceptable barrier
	(D)	(H)	
Less than 3.0) m	Any height	Gantry
Between 3.0	m and 15 m	H less than D H between D and 2D H greater than 2D	Linkmesh fence Hoarding Gantry
Greater than	15 m	Any height	Linkmesh fence

F5 CONSTRUCTION & DEMOLITION HAZARD 1 Not To Scale

- **1.1.4** Viewing windows where used shall be screened with chainlink netting.
- **1.1.5** There shall be no gap between the lower edge of hoardings and the ground that would allow site-water run-off to flow onto a public footway.

1.2 Water hazard fences

- 1.2.1 The fence shall have a height above the outside ground level of at least 1.2 m if solid sheathed or 1.8 m if constructed of netting.
- **1.2.2** No fence shall have external horizontal members or projections which could provide a foothold that are spaced closer than 900 mm vertically.
- **1.2.3** The netting mesh size shall be no greater than 50 mm x 50 mm, and there shall be no openings through which a 100 mm diameter sphere can pass.

1.3 Gantries

- 1.3.1 A gantry shall protect a walkway with a vertical side wall and a horizontal overhead platform.
- **1.3.2** The side wall separating the work-site from the walkway shall comply with Paragraphs 1.1.1 and 1.1.3.
- 1.3.3 Two side walls shall be provided where a gantry is adjacent to a crane pick-up point (i.e. the gantry is clad on the sides in accordance with Paragraph 1.1.3).
- 1.3.4 The outside wall, if immediately adjacent to road traffic, shall be protected by a timber fender of no less than 300 mm x 75 mm, with its lower edge 500 mm above the road surface. An alternative fender may consist of two scaffold tubes spaced vertically at 250 mm centres, with the underside of the lower tube 500 mm above the road surface.

1.3.5 The overhead platform shall have at least 2.4 m clearance above the walkway surface and be constructed of either close-butted timber at least 50 mm thick, or of steel plate having a minimum thickness of 5 mm.

Refer to NZBC B1 for design loadings for gantries.

1.3.6 The platform shall be sufficiently watertight to prevent water dripping on walkway users.

COMMENT:

The territorial authority may require gantries to be artificially lit.

1.4 Toeboards


- 1.4.1 Toeboards for preventing objects falling off storage or access platforms shall be at least as high as the materials stacked on the platform, and no less than 100 mm above the platform. The maximum gap between platform and toeboard shall not exceed 10 mm.
- 1.4.2 If however, stacked materials are otherwise restrained from falling (e.g. if long pieces of timber are held by the handrail posts), the minimum toeboard shall be satisfactory.

COMMENT:

Where toeboards are used as a means of compliance with NZBC F5.3.1, they are not a substitute for gantries or hoardings described in Paragraphs 1.1 and 1.3.








ı	ISSUE	ISSUE NAME	CHANGES	DATE	
Ī	02	Consent		19/08/2019	Drawn By
I					John Ottaway
[john@dataplan.co.nz
I					027 414-3875
Ī					8 Knighton Road
ſ					Hamilton
ľ					






















































Wind = HIGH
Earthquake = ZONE 1

Corrision = ZONE D
Snow = UP to 1.0kPa

15/08/2019 Drawn By
19/08/2019 John Ottaway
john@dataplan.conz
027 414-3675
8 Knighton Road
Hamilton


















Orainage Near Foundations Not To Scale






O Type 2 Catchpit Not To Scale






Cover Greater Than 500mm




Cover Between 375 - 500mm




Cover Between 125 - 375mm

Drainage Trench Backfilling & Bedding
Not To Scale






• SETOUT PLAN 1:100










• FOUNDATION PLAN 1:100

Wind = HIGH | SSUE | ISSUE NAME | CHANGES | DATE | Drawn By |


Earthquake = ZONE 1 | 19/08/2019 | John Ottaway | John@dataplan.conz | 027 414-3675 | 8 Knighton Road | Hamilton | Corrision = ZONE D | Snow = UP to 1.0kPa








RR1 RibRaft Brick Rebate Footing




RR2 RibRaft Shadowclad Footing










RR3 RibRaft Internal Loadbearing Footing




RR4 RibRaft Internal Rib




\\ <i>\\'</i> :	ISSUE	ISSUE NAME	CHANGES	DATE	
Wind = HIGH	02	Consent		19/08/2019	Drawn By
Forth quality - 70NE 1					John Ottaway
Earthquake = ZONE 1					john@dataplan.co.nz
Corrision = ZONE D					027 414-3875
COITISION - ZONE D					8 Knighton Road
Snow = UP to 1.0kPa					Hamilt <i>o</i> n
Show - Or to Loki a					1



Whitianga




RR6 RibRaft Garage Door Footing




RR9 Ribraft Wing Wall Footing















\\ <i>C</i>	ISSUE	ISSUE NAME	CHANGES	DATE	
Wind = HIGH	02	Consent		19/08/2019	Drawn By
Earthquake = ZONE 1					John Ottaway
Lar triquake = ZUNL I					john@dataplan.co.nz
Corrision = ZONE D					027 414-3875
					8 Knighton Road
Snow = $UP to 1.0kPa$					Hamilt <i>o</i> n









RR8 Ribraft Services Penetrations

Through Rib



\\ <i>('</i>	ISSUE	ISSUE NAME	CHANGES	DATE		Г
Wind = HIGH	02	Consent		19/08/2019	Drawn By	
Earthquake = ZONE 1					John Ottaway	
Lar triquake = ZUNE I					john@dataplan.co.nz	
Corrision = ZONE D					<i>0</i> 27 414-3875	
					8 Knighton Road	
Snow = UP to 1.0kPa					Hamilton	

Through Slab


Proposed New Home For Willis & Megan Williams 19 Austin Drive Whitianga

Through Edge Beam



Through Slab

Through Edge Beam





O1 Floor Area

OO2 Deck Area

03 ROOF COVERAGE

003 Roof Coverage

216.59

133.00 m²

242.79


242.79 m²

216.59 m²


Wind = HIGH
Earthquake = ZONE 1

Corrision = ZONE D
Snow = UP to 1.0kPa












DATE

John Ottaway


n@dataplan.co.nz 027 414-3875 8 Knighton Road Hamilton












• ROOF FRAMING PLAN








<u>Symbol</u>	<u>Description</u>	<u>Area</u>
	13mm Aqualine Gib Flat Ceiling	12.76
	13mm Standard Gib Flat Ceiling	190.17
	4.5mm Hardiflex Flat Soffit	13.72
	4.5mm Hardiflex Sloping Soffit	11.88

(4.5mm Hardiflex Soffit)





Wind = HIGH


Earthquake = ZONE 1

Corrision = ZONE D

Snow = UP to 1.0kPa











DATE Wind = **HIGH** John Ottaway Earthquake = **ZONE 1** Corrision = **ZONE D** 8 Knighton Road Hamilton Snow = UP to 1.0kPa









BLOCK 2

BLOCK 3

Demand Calculation Sheet

Job Details Name: Street and Number:

WILLIS & MEGAN WILLIAMS (BLOCK 1) 19 AUSTIN DRIVE

LOT 8 - DPS 85280 Lot and DP Number: City/Town/District: WHITIANGA JOHN OTTAWAY Designer DATAPLAN Company 15-08-2019

Building Specification

2 kPa Floor Loading Foundation Type Slab

Single Cladding Weight Heavy Roof Weight Light Room in Roof Space No Roof Pitch (degrees) 30 Roof Height above Eaves (m) 2.40 Building Height to Apex (m) Ground to Lower Floor (m) 0.225 Average Stud Height (m) 2.570 18 970 Building Length (m) Building Width (m) 7.000 Building Plan Area (m²)

Building Location

Wind Zone = High Earthquake Zone 1

> D & E (Deep to Very Soft) Soil Type Annual Prob. of Exceedance:1 in 500 (Default)

Bracing Units required for Wind

Bracing Units required for Earthquake

Across Single Level 437 1053

Single Level 497

Single Level Along Resistance Sheet

Job Na	ame: WILL	S & MEGA	N WILLIAI	MS (BLOC	K 1)				Wind	EQ
									Den	nand
									437	497
									Achi	eved
Line	Element	Length	Angle	Stud Ht.	Туре	Supplier	Wind	EQ	1073	945
		(m)	(degrees)	(m)			(BUs)	(BUs)	245%	190%
	1	0.55	0	2.570	BL1-H	GIB®	49	51		
	2	1.05	0	2.855	BL1-H	GIB®	106	91		
Α	3	1.06	0	2.855	BL1-H	GIB®	107	92		
	4	1.30	0	2.570	GS2-N	GIB®	119	104		
				Externa	I Lenath =	19.250			381 OK	338 OK
	1	0.64	0	2.570	GS2-N	GIB®	48	43		
В	2	2.38	0	3.229	GS2-N	GIB®	173	152		
									221 OK	195 OK
	1	2.04	0	2.570	GS1-N	GIB®	131	114		<u>-</u>
С	2	3.71	0	2.570	GS2-N	GIB®	340	298		
				Externa	I Length =	19.250			471 OK	412 OK

Single Level Across Resistance Sheet

Job Na	ame: WILL	IS & MEGA	N WILLIAI	MS (BLOC	K 1)				Wind	EQ
									Den	nand
									1053	497
									Achi	eved
Line	Element	Length	Angle	Stud Ht.	Type	Supplier	Wind	EQ	1131	1051
		(m)	(degrees)	(m)			(BUs)	(BUs)	107%	212%
М	1	3.01	0	2.570	BL1-H	GIB®	360	292		
M				Externa	l Length =	7.000			360 OK	292 OK
N	1	2.83	0	2.570	GS1-N	GIB®	183	159		
									183 OK	159 OK
0	1	1.00	0	2.570	BLP-H	GIB®	140	140		
U				Externa	Length =	1.00			140 OK	140 OK
Р	1	2.40	0	2.570	EPB1-1.2	ECOPLY	269	303		
				Externa	I Length =	1.00			269 OK	303 OK
	1	1.11	0	3.400	BL1-H	GIB®	96	81		
Q	2	0.85	0	2.700	BL1-H	GIB®	83	77		
		· ·		Externa	Length =	7.00			179 OK	158 OK

Demand Calculation Sheet

Job Details

WILLIS & MEGAN WILLIAMS (BLOCK 2) Name: 19 AUSTIN DRIVE Street and Number: LOT 8 - DPS 85280 Lot and DP Number: City/Town/District: WHITIANGA Designer: JOHN OTTAWAY Company: DATAPLAN

15-08-2019

Building Specification

2 kPa Floor Loading Foundation Type Slab

Single Cladding Weight Heavy Roof Weight Light Room in Roof Space No Roof Pitch (degrees) 30 Roof Height above Eaves (m) 2.40 Building Height to Apex (m) Ground to Lower Floor (m) 0.225 Average Stud Height (m) 2.570 9 150 Building Length (m) Building Width (m) 6.000

Building Location Wind Zone = High

Building Plan Area (m²)

Earthquake Zone 1

D & E (Deep to Very Soft) Soil Type Annual Prob. of Exceedance: 1 in 500 (Default)

Bracing Units required for Wind

Bracing Units required for Earthquake

Across Along & Across Single Level Single Level 232 540

Single Level Along Resistance Sheet

54.90

Job N	ame: WILL	IS & MEGA	N WILLIAI	MS (BLOC	K 2)				Wind	EQ
									Den	nand
									384	232
									Achi	eved
Line	Element	Length	Angle	Stud Ht.	Type	Supplier	Wind	EQ	822	803
		(m)	(degrees)	(m)			(BUs)	(BUs)	214%	346%
	1	0.69	0	2.570	BL1-H	GIB®	66	65		•
Α	2	2.40	0	2.570	EPB1-1.2	ECOPLY	269	303		
				Externa	Lenath =	9.430			335 OK	367 OK
В	1	3.48	0	2.570	GS2-N	GIB®	318	279		
ь									318 OK	279 OK
	1	0.65	0	2.570	BL1-H	GIB®	61	61		
С	2	0.98	0	2.570	BL1-H	GIB®	107	94		
				Externa	Length =	9.430			169 OK	156 OK

Single Level Across Resistance Sheet

Job N	ame: WILL	IS & MEGA	AN WILLIAI	MS (BLOC	K 2)				Wind	EQ
									Den	nand
									540	232
									Achi	eved
Line	Element	Length	Angle	Stud Ht.	Type	Supplier	Wind	EQ	625	536
		(m)	(degrees)	(m)			(BUs)	(BUs)	116%	231%
М	1	4.02	0	2.570	GS1-N	GIB®	259	225		
M				Externa	l Lenath =	6.000			259 OK	225 OK
N	1	2.30	0	2.570	GS2-N	GIB®	210	185		
IN									210 OK	185 OK
0	1	1.30	0	2.570	BL1-H	GIB®	155	126		
0				Externa	l Length =	6.000			155 OK	126 OK

Demand Calculation Sheet

Job Details

WILLIS & MEGAN WILLIAMS (BLOCK 3) Name: 19 AUSTIN DRIVE Street and Number: LOT 8 - DPS 85280 Lot and DP Number: City/Town/District: WHITIANGA JOHN OTTAWAY Designer: Company DATAPI AN 15-08-2019

Building Specification

Floor Loading 2 kPa Foundation Type Slab Single Cladding Weigh Heavy Roof Weight Light Room in Roof Space Roof Pitch (degrees) 30 Roof Height above Eaves (m) 2.40 Building Height to Apex (m) 5.0 Ground to Lower Floor (m) 0.225 Average Stud Height (m) 2.570 7 000 Building Length (m) Building Width (m) 6.000 Building Plan Area (m²) 42.54

Building Location

Wind Zone = High Earthquake Zone 1

D & E (Deep to Very Soft) Soil Type Annual Prob. of Exceedance:1 in 500 (Default)

Bracing Units required for Wind

Bracing Units required for Earthquake

Along & Across Single Level 428 180 384

Single Level Along Resistance Sheet

Job N	ame: WILL	IS & MEGA	N WILLIA	MS (BLOC	K 3)				Wind	EQ
									Der	nand
									384	180
									Ach	ieved
Line	Element	Length	Angle	Stud Ht.	Type	Supplier	Wind	EQ	490	427
		(m)	(degrees)	(m)			(BUs)	(BUs)	128%	237%
	1	2.12	0	2.570	GS1-N	GIB®	137	119		•
Α	2	2.11	0	2.570	GS1-N	GIB®	136	118		
				Externa	al Lenath =	7.000			273 OK	237 OK
	1	0.99	0	2.570	BL1-H	GIB®	109	95		
В	2	0.99	0	2.570	BL1-H	GIB®	109	95		
				F. 1	I Length =	7.000		•	218 OK	190 OK

Single Level Across Resistance Sheet


Job Name: WILLIS & MEGAN WILLIAMS (BLOCK 3)								Wind	EQ	
									Der	nand
									428	180
									Ach	ieved
Line	Element	Length	Angle	Stud Ht.	Туре	Supplier	Wind	EQ	599	523
		(m)	(degrees)	(m)			(BUs)	(BUs)	140%	291%
	1	3.71	0	2.570	GS2-N	GIB®	340	298		
М				Externa	I Lenath =	6.000			340 OK	298 OK
N	1	4.02	0	2.570	GS1-N	GIB®	259	225		
IN									259 OK	225 OK

Wind = **HIGH** Earthquake = **ZONE 1** Corrision = **ZONE D**

Snow = **UP to 1.0kPa**

John Ottaway 8 Knighton Road Hamilton






. Code	Symbol	Description	Qty
1-Lightir	າg		
101	(A)	Interior LED Downlight IC Rated	48
102	(B)	Ceiling Mounted Hanging Pendant Light	4
103	*	Wall Mounted Interior LED Light	2
104	Ø	Soffit Mounted LED Downlight IC Rated	7
105	承	Wall Mounted Exterior LED Light	7
2-Switc	hing		
201	φ̂	Single Switch	13
202	20^	Double Switch	1
203	3 O ^	Triple Switch	2
204	40^	Quad Switch	1
205	6 Q ^	6 Switch	2
3-Powe	rSupply		
201	24	Double Power Point	27
202	pw Y	Dishwasher Power Supply	1
203	FR Y	Fridge Power Supply	1
204	9	Garage Door Power Supply	1
205	HPE Y	Heat Pump External PowerSupply	1
206	HPI Y	Heat Pump Internal Power Supply	1
207	HTR Y	Heated Towel Rail Power Supply	2
208	HP Y	Hot Plate Power Supply	1
209	Oven Y	Oven Power Supply	1
210	Hood	Range Hood PowerSupply	1
211	Waste ↓↓	Waste Disposal Power Supply	1
4 - Comn	nunication		
401	0	Smoke Alarm	3
402	Alarm	Alarm System	1
403	$\overline{\downarrow}_{\scriptscriptstyle TV}$	TV Jack Point	1
5 - Venti	ation		
501	8	Manrose SF200T 100mm Extract Kit With Timer 30 litres/sec	2
6 - Misc			
601		Switch Board	1


• ELECTRICAL PLAN 1:100








• FLOOR COVERING PLAN 1:100













• REFERENCE PLAN 1:500
















• REFERENCE PLAN 1:500









\\ <i>('</i>	ISSUE	ISSUE NAME	CHANGES	DATE	
Wind = HIGH	02	Consent		19/08/2019	Drawn By
Earthquake = ZONE 1					│ John Ottaway│
Lar triquake = ZUNL I					john@dataplan.co.nz
Corrision = ZONE D					027 414-3875
					8 Knighton Road
Snow = UP to 1.0kPa					Hamilton






© REFERENCE PLAN 1:500








\\	ISSUE	ISSUE NAME	CHANGES	DATE		Г
Wind = HIGH	02	Consent		19/08/2019	Drawn By	
onth audica - 70NE 1					John Ottaway	
Earthquake = ZONE 1					john@dataplan.co.nz	
Corrision = ZONE D					027 414-3875	
					8 Knighton Road	
Snow = $UP to 1.0kPa$					Hamilt <i>o</i> n	



	EXTERIOR OPENING LISTING									
ID	Wall Structure	Finish	Glazing	Jamb	Lintel	Fixing				
W <i>O</i> 1	EXT 90mm WALL (Batts - Gib)	Selected Entrance Door	N/A	20mm Liner	150x90 hy90	Fixing 'F'				
W <i>O</i> 2	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed	20mm Liner	200x90 hy90	Fixing 'G'				
W <i>0</i> 3	EXT 90mm WALL (Batts - Gib)	Sectional Garage Door	N/A	20mm Liner	300x90 hy0NE	Fixing 'H'				
W <i>O</i> 4	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	15 <i>0</i> x9 <i>0</i> hy9 <i>0</i>	Fixing 'E'				
W <i>0</i> 5	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	15 <i>0</i> x9 <i>0</i> hy9 <i>0</i>	Fixing 'E'				
W06	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	200x90 hy90	Fixing 'G'				
W <i>0</i> 7	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	240x90 hy90	Fixing 'G'				
W08	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety Etchlite	20mm Liner	15 <i>0</i> x9 <i>0</i> hy9 <i>0</i>	Fixing 'F'				
W09	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	15 <i>0</i> x9 <i>0</i> hy9 <i>0</i>	Fixing 'E'				
W10	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	150x90 hy90	Fixing 'E'				
W12	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	200x90 hy90	Fixing 'G'				
W13	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	15 <i>0</i> x9 <i>0</i> hy9 <i>0</i>	Fixing 'F'				
W14	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	300x90 hy90	Fixing 'H'				
W15	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	200x90 hy90	Fixing 'G'				
W16	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	200x90 hy90	Fixing 'G'				
W17	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	150x90 hy90	Fixing 'E'				
W18	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety	20mm Liner	150x90 hy90	Fixing 'E'				
W19	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed	20mm Liner	15 <i>0</i> x9 <i>0</i> hy9 <i>0</i>	Fixing 'F'				
W20	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety Etchlite	20mm Liner	15 <i>0</i> x9 <i>0</i> hy9 <i>0</i>	Fixing 'F'				
W21	EXT 90mm WALL (Batts - Gib)	Powdercoated	Double Glazed Safety Etchlite	20mm Liner	150x90 hy90	Fixing 'F'				

© EXTERIOR DOOR & WINDOW SCHEDULE 1:100



	INTERIOR OPENING LISTING										
ID	Wall Structure	Door Type	Hanging	Jamb	Glazing	Lintel	Fixing				
DO1	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single Hung	20mm Liner	N/A	15 <i>0</i> x9 <i>0</i> hy9 <i>0</i>	Fixing 'E'				
DO2	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single Hung	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
DO2	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single Hung	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D03	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single Hung	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D04	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single Hung	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D <i>O</i> 5	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	3 Door Slider	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D <i>O</i> 5	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Double Hung	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D06	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single Hung	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D07	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Double Hung	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D08	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single Slider	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D09	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single Hung	20mm Liner	N/A	150x90 hy90	Fixing 'E'				
D10	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single Hung	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D11	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single CA Slider	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				
D12	INT 90mm WALL (Gib - Gib)	Hollow Core Flush Door	Single CA Slider	20mm Liner	N/A	90x45 H1.2 MSG8	Fixing 'E'				

• INTERIOR DOOR SCHEDULE
1:100



Wind = HIGH

Earthquake = ZONE 1


Corrision = ZONE D

Snow = UP to 1.0kPa

NOTE: Zone D includes all offshore islands, the area within 500m of the coastline of Zone New Zealand, and those areas shown in white. The map shall be read in Houhora Heads conjunction with 4.2.2 NZS 3604:2011 Kaitaia Ahipara **Exposure Zones** Opononi Zone B Whangarei Baylys Beach Zone C Dargaville Zone D Muriwai Beach Whitianga Auckland Kopu Ngatea - Whangamata Tuakau Waihi Maramarua Katikati Hamilton Whakatane Tauriko _ Te Puke Raglan Otorohanga -Rotorua 😜 Whatatutu Zone Zone Waerengaahika Gisborne New Plymouth Inglewood Wairoa Kaponga Taradale Waverley Hastings Marton Sanson -Porangahau Linton Castlepoint Wellington Wainuiomata


Exposure Map North Island
Not To Scale

DURABILITY FLOW CHART




O Durability Flow Chart
Not To Scale












Wind = HIGH
Earthquake = ZONE 1

Corrision = ZONE D
Snow = UP to 1.0kPa











Lintel / Stud ToTop Plate Fixings
Not To Scale


Wind = **HIGH** John Ottaway Earthquake = **ZONE 1** n@dataplan.co.nz 027 414-3875 8 Knighton Road Hamilton Corrision = ZONE D Snow = **UP to 1.0kPa**



FIXING TYPE C 2.4kN








1/10g x 80mm LUMBERLOK BLUE SCREW (Timber Purlin) (Rafter Or Truss Top Chord 90x45 Block Fixed To Top Chord / Rafter With 4 / 75x3.15mm Nails Elevation

STANDARD FIXING

SPLICE FIXING


O TYPE C Purlin Fixing Not To Scale
















O Bottem Plate Fixing Not To Scale













HEM

NOTE HOOKS € HEMS REQUIRED ON ALL FLASHINGS REGARDLESS OF WIND ZONE




KICK OUT BIRDS BEAK

O Hook & Hem Detail
Not To Scale



O Cavity Batten Spacer Not To Scale



O Garage Door Threshold Not To Scale

Wind = HIGH


Earthquake = ZONE 1

Corrision = ZONE D

Snow = UP to 1.0kPa









WINDOW ELEVATION

(CORNER GUARDS - Masons Plastic Corner Guard)



WINDOW HEAD INSTALLATION



WINDOW SILL INSTALLATION

• Window Tape Details


Not To Scale



ISSUE	ISSUE NAME	CHANGES	DATE	
02	Consent		19/08/2019	Drawn By
				│ John Ottaway│
$\overline{}$				john@dataplan.co.nz
				027 414-3875
				8 Knighton Road
				Hamilton
	02	O2 Consent	O2 Consent	02 Consent 19/08/2019









Tray Roofing

© Eaves Overhang 1:5



Tray Roofing






Tray Roofing

• Eaves No Overhang 1:5



\\ <i>('</i> :	ISSUE	ISSUE NAME	CHANGES	DATE	
Wind = HIGH	02	Consent		19/08/2019	Drawn By
Earthquake = ZONE 1					John Ottaway
Lar triquake = ZUNL I					john@dataplan.co.nz
Corrision = ZONE D					027 414-3875
					8 Knighton Road
Snow = UP to 1.0kPa					Hamilt <i>o</i> n





(Pipe Up To85mm Max) (Clip Fixing System) (EPDM Flexible Cone Sleeve) Malleable Flange, Rivet Or Screw Fixed And Sealed To Roofing \
Profile. Fit Neoprene Washers To All Screw Fixings. Fitted on I-Timber Purlin) 45deg Angle In Plan. Refer To MRM Code Of Practice.) (Thermakraft 215 Roof Underlay) (Coloursteel Tray Roofing) (Clip Fixing System) (Truss Top Chord Or Rafter Roof Pitch 10° min - 45° max Malleable Flange, Rivet Or Screw Fixed And Sealed To Roofing Profile. Fit Neoprene Washers To All Screw Fixings. Fitted on (EPDM Flexible Cone Sleeve) 45deg Angle In Plan. Refer To MRM Code Of Practice. (Coloursteel Tray Roofing) (Timber Purlin) Timber Purlin) (Thermakraft 215 Roof Underlay) (Pipe Up To85mm Max) (Truss Top Chord Or Rafter) (Truss Top Chord Or Rafter) Tray Roofing

Penetration Up To 85mm
1:5

John Ottaway

8 Knighton Road

Wind = HIGH SSUE ISSUE NAME CHANGES DA


Earthquake = ZONE 1

Corrision = ZONE D

Snow = UP to 1.0kPa











Wind = HIGH


Earthquake = ZONE 1

Corrision = ZONE D


Snow = UP to 1.0kPa

(Coloursteel Ridge Flashing)





O Slab Base




BRICK VENEER

Pipe Penetration
1:2




Wind = HIGH	ISSUE	ISSUE NAME	CHANGES	DATE	
wina = nig n	02	Consent		19/08/2019	Drawn By
Earthquake = ZONE 1					John Ottaway
Lar triquake = ZUNL I					john@dataplan.co.nz
Corrision = ZONE D					027 414-3875
COITISION - ZOINE D					8 Knighton Road
Snow = UP to 1.0kPa					Hamilt <i>o</i> n
JIIOW - OF LO I.OKF A					1















• Flat Soffit




• Window Jamb
1:2




\\ <i>\\</i> '	ISSUE	ISSUE NAME	CHANGES	DATE	
Wind = HIGH	02	Consent		19/08/2019	Drawn f
Earthquake = ZONE 1					John Ottawa
Lar triquake = ZUNE I					john@dataplan.co.i
Corrision = ZONE D					027 414-387
					8 Knighton Roa
Snow = UP to 1.0kPa					Hamilto
					l






Meterbox Head 1:2



BRICK VENEER

Meterbox Jamb 1:2



(Metal Meter Box)

BRICK VENEER

• Meterbox Sill 1:2




Wind = HIGH


Earthquake = ZONE 1

Corrision = ZONE D

Snow = UP to 1.0kPa








• Internal Corner 1:2




IG PRACA		Wind = HIGH	ISSUE O2	ISS
MONER		Earthquake = ZONE 1		
h.govt.nz		Corrision = ZONE D		
ONFIDEN	ALL DIMENSIONS, INVERTS, GROUND LINES & LEVELS, ANGLES, ETC ARE TO BE CHECKED AND CONFIRMED ON-SITE BEFORE COMMENCING ANY WORK	Snow = UP to 1.0kPa		











JUNCTION BETWEEN BRICK VENEER & SHADOWCLAD

• Internal Corner 1:2




Brick Veneer

• Flush Soffit










Garage Door Head
1:2




Garage Door Jamb




\\ <i>\\</i> :	ISSUE	ISSUE NAME	CHANGES	DATE	
Wind = HIGH	02	Consent		19/08/2019	Drawn By
Earthquake = ZONE 1					John Ottaway
Lar inquake = ZUNE I					john@dataplan.co.nz
Corrision = ZONE D					027 414-3875
CONTISION - ZONE D					8 Knighton Road
Snow - IID to 10LDo					Hamilt <i>o</i> n






Shadowclad Cavity Window Head

2 Stop ends to head flashing terminations




1 Treat all cut edges with Holdfast® Metalex® Clear

Shadowclad Cavity Window Sill



Proposed New Home For Willis & Megan Williams 19 Austin Drive Whitianga






Note:


- 1. Treat all cut edges with Holdfast® Metalex® Clear
- 2. 50mm strip of neutral cure silicon sealant must be provided at the termination point of all Z flashings at windows, corner boxes, etc.

Shadowclad Cavity Window Jamb Not To Scale




1. Do not nail through weather grooves

Shadowclad Cavity Vertical Joint (Cover batten 2) Not To Scale




Shadowclad Cavity Soffit 2
Not To Scale



Vertical section

Shadowclad Cavity Base (Concrete)X
Not To Scale






Cavity batten Wall underlay Shadowclad

Flashing tape all round

Shadowclad Cavity Pipe Penetration
Not To Scale


\\ <i>\\</i> '	ISSUE	ISSUE NAME	CHANGES	DATE	
Wind = HIGH	02	Consent		19/08/2019	Drawn B
Earthquake = ZONE 1					John Ottawa
Lai ti iquake - ZUNL I					john@dataplan.co.r
Corrision = ZONE D					027 414-387
					8 Knighton Roa
Snow = UP to 1.0kPa					Hamilto
J J. 40 110 111 01	I		1		I






Note: Single spans of Shadowclad® must not exceed 600mm (e.g. Below windows or on Balustrades)

Shadowclad Cavity Framing Layout Not To Scale




Shadowclad Cavity Batten Setout Not To Scale



Proposed New Home For Willis & Megan Williams 19 Austin Drive Whitianga





Framing Centres


600

600

600

Shadowclad Cavity Fixing Setout Not To Scale

50 mm min. sheet overhang (refer SC042, SC044 & SC046 as appropriate)







GIB EzyBrace® Systems specification GS1-N

Specification code	Minimum length (m)	Lining requirement
GS1-N	0.4	Any 10mm or 13mm GIB® Standard plasterboard to one side only

WALL FRAMING

Wall framing to comply with;

- NZBC B1 Structure B1/AS1 Clause 3 Timber (NZS 3604:2011).
- NZBC B2 Durability B2/AS1 Clause 3.2 Timber (NZS 3602).

Framing dimensions and height as determined by NZS 3604:2011 stud and top plate tables for load bearing and non-bearing walls. The use of kiln dried stress graded timber is recommended.

BOTTOM PLATE FIXING

Timber floor

Pairs of hand driven 100 x 3.75mm nails at 600mm centres; or three power driven 90 x 3.15mm nails at 600mm centres.

Concrete floor

Internal Wall Bracing Lines: In accordance with the requirements of NZS 3604:2011 for internal wall plate fixing or 75×3.8 mm shot fired fasteners with 16mm discs spaced at 150mm and 300mm from end studs and 600mm centres thereafter.

External Wall Bracing Lines: In accordance with the requirements of NZS 3604:2011 for external wall bottom plate fixing.

WALL LINING

- Any 10mm or 13mm GIB® plasterboard lining.
- Sheets can be fixed vertically or horizontally.
- Sheet joints shall be touch fitted.
- Use full length sheets where possible.

PERMITTED ALTERNATIVES

For permitted GIB® plasterboard alternatives refer to p. 5 in GIB EzyBrace® Systems literature.

FASTENING THE LINING

Fasteners


32mm x 6g GIB® Grabber® High Thread Screws, 32mm x 7g GIB® Grabber® Dual Thread Screws or 30mm GIB® Nails. If using the GIBFix® Angle use only 32mm x 7g GIB® Grabber® Dual Thread Screws.

Fastener centres

50,100,150, 225, 300mm maximum from each corner and 150mm thereafter around the perimeter of the bracing element. For vertically fixed sheets place fasteners at 300mm maximum centres to intermediate sheet joints. For horizontally fixed sheets place single fasteners to the sheet edge where it crosses the stud. Use daubs of GIBFix® adhesive at 300mm maximum centres to intermediate studs. Place fasteners no closer than 12mm from paper bound sheet edges and 18mm from any sheet end or cut edge.

JOINTING

Joint strength is important in delivering bracing system performance. All fastener heads stopped and all sheet joints GIB® Joint Tape reinforced and stopped in accordance with the GIB® Site Guide.



In order for GIB® systems to perform as tested, all components must be installed exactly as prescribed. Substituting components produces an entirely different system and may seriously compromise performance. Follow the specifications. This specification sheet is issued in conjunction with the publication GIB EzyBrace® Systems



GIB EzyBrace® Systems specification GS2-N

Specification code	Minimum length (m)	Lining requirement
GS2-N	0.4	Any 10mm or 13mm GIB® Standard plasterboard fixed to each side of the wall framing

WALL FRAMING

Wall framing to comply with;

- NZBC B1 Structure B1/AS1 Clause 3 Timber (NZS 3604:2011).
- NZBC B2 Durability B2/AS1 Clause 3.2 Timber (NZS 3602).

Framing dimensions and height as determined by NZS 3604:2011 stud and top plate tables for load bearing and non-bearing walls. The use of kiln dried stress graded timber is recommended.

BOTTOM PLATE FIXING

Timber Floor

Pairs of hand driven 100 x 3.75mm nails at 600mm centres; or three power driven 90 x 3.15mm nails at 600mm centres.

Concrete floor

Internal Wall Bracing Lines: In accordance with the requirements of NZS 3604:2011 for internal wall plate fixing or 75 x 3.8mm shot fired fasteners with 16mm discs spaced at 150mm and 300mm from end studs and then 600mm centres thereafter.

WALL LINING

- A layer of 10mm or 13mm GIB® plasterboard to each side of the wall.
- Sheets can be fixed vertically or horizontally.
- Sheet joints shall be touch fitted.

Use full length sheets where possible.

PERMITTED ALTERNATIVES

For permitted GIB® plasterboard alternatives refer to p. 5 in GIB EzyBrace® Systems literature.

FASTENING THE LINING

Fastener


32mm x 6g GIB® Grabber® High Thread Screws,32mm x 7g GIB® Grabber® Dual Thread Screws or 30mm GIB® Nails. If using the GIBFix® Angle use only 32mm x 7g GIB® Grabber® Dual Thread Screws.

Fastener centres

50,100,150, 225, 300mm maximum from each corner and 150mm thereafter around the perimeter of the bracing element. For vertically fixed sheets place fasteners at 300mm maximum centres to intermediate sheet joints. For horizontally fixed sheets place single fasteners to the sheet edge where it crosses the stud. Use daubs of GIBFix® adhesive at 300mm maximum centres to intermediate studs. Place fasteners no closer than 12mm from paper bound sheet edges and 18mm from any sheet end or cut edge.

JOINTING

Joint strength is important in delivering bracing system performance. All fastener heads stopped and all sheet joints GIB® Joint Tape reinforced and stopped in accordance with the GIB® Site Guide.



In order for GIB® systems to perform as tested, all components must be installed exactly as prescribed. Substituting components produces an entirely different system and may seriously compromise performance. Follow the specifications. This specification sheet is issued in conjunction with the publication GIB EzyBrace® Systems

O GIB-EzyBrace-System-GS2-N Not To Scale



Wind = HIGH Earthquake = ZONE 1 Corrision = ZONE D Snow = UP to 1.0kPa

	ISSUE	ISSUE NAME	CHANGES	DATE	
ı	02	Consent		19/08/2019	Drawn By
					John Ottaway
ı					john@dataplan.co.nz
)					027 414-3875
					8 Knighton Road
					Hamilton
•					



GIB EzyBrace® Systems specification BL1-H

Specification code	Minimum length (m)	Lining requirement	Other requirements
BL1-H	0.4	10mm or 13mm GIB Braceline® to one side only	Hold downs

WALL FRAMING

Wall framing to comply with;

- NZBC B1 Structure B1/AS1 Clause 3 Timber (NZS 3604:2011).
- NZBC B2 Durability B2/AS1 Clause 3.2 Timber (NZS 3602).

Framing dimensions and height as determined by NZS 3604:2011 stud and top plate tables for load bearing and non-bearing walls. The use of kiln dried stress graded timber is recommended.

BOTTOM PLATE FIXING

Timber floor

Use panel hold downs at each end of the bracing element. The GIB HandiBrac® is recommended. See details in GIB EzyBrace® Systems or GIB® Site Guide.

Pairs of hand driven 100 \times 3.75mm nails at 600mm centres; or Three power driven 90 \times 3.15mm nails at 600mm centres.

Concrete floor

Use panel hold downs at each end of the bracing element. The GIB HandiBrac® is recommended. See details in GIB EzyBrace® Systems or GIB® Site Guide. Within the length of the bracing element bottom plates are to be fixed in accordance with the requirements of NZS 3604:2011.

WALL LINING

A layer of 10mm or 13mm GIB Braceline[®]

Use full length sheets where possible.

- Sheets can be fixed vertically or horizontally.
- Sheet joints shall be touch fitted.

PERMITTED ALTERNATIVES

For permitted GIB® plasterboard alternatives refer to p. 5 in GIB EzyBrace® Systems literature.

FASTENING THE LINING

Fasteners


32mm x 6g GIB® Grabber® High Thread Screws or 32mm x 7g GIB® Grabber® Dual Thread Screws. If using the GIBFix® Framing System or if fastening through GIBFix® Angles use only 32mm x 7g GIB® Grabber® Dual Thread Screws.

Fastener centres

50,100,150, 225, 300mm from maximum each corner and 150mm thereafter around the perimeter of the bracing element. For vertically fixed sheets place fasteners at 300mm maximum centres to the sheet joint. For horizontally fixed sheets place single fasteners to the sheet edge where it crosses the stud. Use daubs of GIBFix® adhesive at 300mm maximum centres to intermediate studs. Place fasteners no closer than 12mm from paper bound sheet edges and 18mm from any sheet end or cut edge.

JOINTING

Joint strength is important in delivering bracing system performance. All fastener heads stopped and all sheet joints GIB® Joint Tape reinforced and stopped in accordance with the GIB® Site Guide.



In order for GIB® systems to perform as tested, all components must be installed exactly as prescribed. Substituting components produces an entirely different system and may seriously compromise performance. Follow the specifications. This specification sheet is issued in conjunction with the publication GIB EzyBrace® Systems

OGIB-EzyBrace-System-BL1-H Not To Scale

GIB EzyBrace® Systems specification BLP-H

Specification code	Minimum length (m)	Lining requirement	Other requirements
BLP-H	0.4	10mm or 13mm GIB Braceline® to one side of the frame plus minimum 7mm structural plywood manufactured to AS/NZ 2269.0 :2012 to the other side	Hold downs

WALL FRAMING

Wall framing to comply with;

- NZBC B1 Structure; B1/AS1 Clause 3 Timber (NZS 3604:2011).
- NZBC B2 Durability B2/AS1 Clause 3.2 Timber (NZS 3602).

Framing dimensions and height as determined by NZS 3604:2011 stud and top plate tables for load bearing and non-bearing walls. The use of kiln dried stress graded timber is recommended.

BOTTOM PLATE FIXING

Timber floor

Use panel hold downs at each end of the bracing element. The GIB® HandiBrac is recommended. See details in GIB EzyBrace® Systems or GIB® Site Guide.

Pairs of hand driven 100 \times 3.75mm nails at 600mm centres; or Three power driven 90 \times 3.15mm nails at 600mm centres.

Concrete floor

Use panel hold downs at each end of the bracing element. The GIB HandiBrac® is recommended. See details in GIB EzyBrace® Systems or GIB® Site Guide. Within the length of the bracing element bottom plates are to be fixed in accordance with the requirements of AS/NZ 2269/0:2012.

WALL LINING

- A layer of 10mm or 13mm GIB Braceline® to one side of the wall plus minimum 7mm structural plywood manufactured to AS/NZS 2269.0 :2012 to the other side.
- Sheets can be fixed vertically or horizontally.
- Plywood is to be fixed vertically with edges supported.
- Sheet joints shall be touch fitted.
- Use full length sheets where possible.

PERMITTED ALTERNATIVES

For permitted GIB® plasterboard alternatives refer to p. 5 in GIB EzyBrace® Systems literature.

FASTENING THE LINING

Fasteners


GIB Braceline® side: 32mm x 6g GIB® Grabber® High Thread Screws or 32mm x 7g GIB® Grabber® Dual Thread Screws. Plywood: 50 x 2.8mm Galv or Stainless steel annular grooved FH nails. If using the GIBFix® Framing System or if fastening through GIBFix® Angles use only 32mm x 7g GIB® Grabber® Dual Thread Screws.

Fastener centres

GIB® Plasterboard side: 50,100,150, 225, 300mm from each corner and then 150mm thereafter around the perimeter of the bracing element. For vertically fixed sheets place fasteners at 300mm centres to the intermediate sheet joints. For horizontally fixed sheets place single fasteners to the sheet edge where it crosses the stud. Use daubs of GIBFix® adhesive at 300mm centres to intermediate studs. Place fasteners no closer than 12mm from paper bound sheet edges and 18mm from any sheet end or cut edge. Plywood side: 150mm centres to the perimeter of each sheet. GIB® corner fastener pattern does not apply to the plywood side. 300mm centres to intermediate studs.

JOINTING

Joint strength is important in delivering bracing system performance. All fastener heads stopped and all sheet joints GIB® Joint Tape reinforced and stopped in accordance with the GIB® Site Guide.



In order for GIB® systems to perform as tested, all components must be installed exactly as prescribed. Substituting components produces an entirely different system and may seriously compromise performance. Follow the specifications. This specification sheet is issued in conjunction with the publication GIB EzyBrace® Systems

O GIB-EzyBrace-System-BLP-H Not To Scale



Wind = HIGH SSUE ISSUE NAME CHA


Earthquake = ZONE 1


Corrision = ZONE D


Snow = UP to 1.0kPa



















\\ <i>\\\</i> :	ISSUE	ISSUE NAME	CHANGES	DATE	
Wind = HIGH	02	Consent		19/08/2019	Drawn By
Earthquake = ZONE 1					John Ottaway
•					john@dataplan.co.nz
Corrision = ZONE D					027 414-3875
					8 Knighton Road
Snow = UP to 1.0kPa					Hamilt <i>o</i> n














Wind = **HIGH** John Ottaway Corrision = ZONE D 8 Knighton Road Snow = UP to 1.0kPa










(GRIPSET® G38 or GRIPSET®)
(GRIPSET® SB Sealant)
(Selected Tiles Fixed)
(With Laticrete 4XLT)
(GRIPSET® SB Sealant)
(GRIPSET® SB Sealant)

(GRIPSET® SB Sealant)

(Vanity Top)



Waterstop At Tile Termination

