


How does Voyage decking stack up?




PERMADECK HIDDEN FASTENER

Each Fastener comes with a Marine Grade Stainless Steel Screw for use on wooden joists. To fix to aluminium subframes you will need to source self-tapping screws.



PROFILES

Slotted-edge decking gives a clean, fastener-free appearance to the surface of your deck. Permadeck hidden fasteners are a perfect way to discreetly secure deck boards to joists using the slotted edges.



ALL DECKORATORS DECKING



MADE IN USA

VOYAGE DECKING PROPERTIES



PROPERTY	TEST METHOD	RESULT
Coefficient of Thermal Expansion	ASTM D 696	0.94x10 ⁻⁵ mm/mm *Degree Celcius
Flexural Modulus (MOE)	ASTM D 6109	2,799 Mpa
Flexural Strength (MOR)	ASTM D 6109	27.58 Mpa
Screw Head Pull-through (Ultimate)	ASTM D 1761	182 Kilograms
Decay (Brown and White Rot)	ASTM D 2107-05	No effect
Termites (Formosan Subterranean)	ASTM D 3345-08	No effect
Slip Resistance	AS 4586-2013	Class: P5
Flame Spread (Capped)	ASTM E-84	155 (Class C)
Uplift Resistance with Stowaway Fastener	ASTM E 330	488 kg/m ²
Moisture Absorption	ASTM D	<0.4% (Full Submerged for 24 hours - Extreme Condition)
Weight Per Lineal Foot		2.38 Kilograms per meter
Span/Load Rating		Joist Spar 406mm on-center with a maximum area load rating of 488 kg/m ²
Stair Tread Rating		Stringers span 229 mm on-center with a two-span condition minimum. Maximum Point load is 136 kilograms



For more information contact:

Craig: **0292 444 086**

Wayne: **021 331 653**

Email: info@permadeck.co.nz



Address:

40 Hotuhotu Street,

Tauriko, Tauranga

New Zealand 3110

©2024 UFP Retail Solutions, LLC. All rights reserved. Deckorators is a registered trademark of Deckorators, Inc. 15315_5/24



VOYAGE AND VENTURE DECKING



For more information contact:

Craig: **0292 444 086**

Wayne: **021 331 653**

Email: info@permadeck.co.nz

VOYAGE DECKING



Learn more about
Voyage Decking here:




SURESTONE™ TECHNOLOGY

- DURABLE CAP** (Icon: flame)
- LOW MAINTENANCE** (Icon: crossed wrench and screwdriver)
- WATER & GROUND SAFE** (Icon: water drop and checkmark)
- LOW THERMAL MOVEMENT** (Icon: thermometer with arrows)
- Lightweight** (Icon: leaf)
- 25 | 25 YEAR LIMITED WARRANTY** (Circular seal)
- STRUCTURAL • STAIN & FADE • LIMITED WARRANTY** (Circular seal)

Virtually no thermal movement
Virtually no moisture absorption

Unique decking suitable for residential, commercial and marine applications.



- Vertical grain with enhanced traction
- Unique cap contains infrared reflective materials to reduce solar heat gain
- Micro-embossing reduces the surface-to-skin contact



Width: 140mm
Length: 5.8 m



Width: 140mm
Length: 5.8 m

VENTURE DECKING



TRADITIONAL COMPOSITE

Proudly manufactured in the U.S.A., using 95% recycled plastic and renewable sawdust

- DURABLE CAP** (Icon: flame)
- LOW MAINTENANCE** (Icon: crossed wrench and screwdriver)
- STAIN & FADE RESISTANCE** (Icon: sun)
- 25 | 25 YEAR LIMITED WARRANTY** (Circular seal)
- STRUCTURAL • STAIN & FADE • LIMITED WARRANTY** (Circular seal)

Capped on three sides through the groove


ALL DECKORATORS DECKING



The best combination of value and performance



Width: 140mm
Length: 5.8 m



Width: 140mm
Length: 5.8 m